

**IN THE CLAIMS**

1. (currently amended) An electronic headset, comprising:

(a) a housing having at least one opening therein and an endface at which said at least one opening terminates, said housing being adaptable to be arranged at least partially within an ear of a user such that said at least one opening is directed toward the auditory canal within the user's ear;

(b) electronic circuitry arranged within said housing, said circuitry being adapted to transmit sound through said at least one opening of said housing;

(c) a mounting member connected to said housing and being adapted to rest within ~~an external cavity of the user's~~ ear; and

(d) a clamp connected to said housing for pivotal movement away from said end face ~~between a disengaged position~~ where it is remote from the user's ear, and an movement toward said end face where it is in contact with the ~~rear side of user's earlobe~~ whereby secured assembly of the housing on the ear ~~is~~ can be obtained.

2. (currently amended) The electronic headset of claim 1 wherein said housing includes an extended portion, said at least one opening arranged through said extended portion, said extended portion arranged substantially adjacent the auditory canal of a user's ear but does not entirely occlude the auditory canal.

3. (original) The electronic headset of claim 2 wherein said mounting member is connected to said housing at said extended portion.

4. (original) The electronic headset of claim 1 wherein said electronic circuitry comprises an electroacoustic transducer.

5. (original) The electronic headset of claim 1 wherein said housing includes an inner member and an outer member connected to the inner member to define a chamber for mounting the electronic circuitry therein.

6. (original) The electronic headset of claim 1 wherein said mounting member includes an arcuate neck portion which provides a resting surface for the housing against the user's ear.

7. (currently amended) The electronic headset of claim 1 wherein said mounting members has at least one bore formed therein, said at least one bore being substantially aligned with said at least opening to form a conduit for the sound transmitted by said electronic circuitry.

8. - 14. (cancelled).

15. (original) An ear mounting assembly for electronic components having means for transmitting audio sounds, signals and communications to removably secure the electronic components in the cavity and on the lobe of the user's ear to enable the sounds, signals and communications to pass along with other sounds to the auditory canal of the user's ear comprising:

(a) a housing having an inner member and an outer member connected to the inner member to define a chamber for mounting the electronic components in the housing,

(b) said inner member having an inner face and an outer face, a main passageway extending transversely thereof, said passageway having one end adjacent the chamber and another

end opening onto the inner face for transmitting the audio sounds, signals and communications, and a connecting means on the inner surface about the opening formed by the passageway,

(c) an inner section having an arcuate section, and a connector about the end of the arcuate section for connecting the ear section to the inner surface of the inner housing, and a shaped ear pad connected to the end of the arcuate section remote from the connected end of the arcuate section, and a bore extending end-to-end through the ear section communicating at one end with the enlarged passageway and at the other end open for transmitting the audio sounds, signals and communications, and

(d) a clamping assembly pivotally connected to the inner housing remote from the ear section removable from a disengaged position to an engaged position with the lobe of the user's ear for detachably connecting the ear mounting member and the electronic components therein into operative relation with the auditory canal of the ear to pass said sounds, signals and communications to the auditory canal without interfering with the ability of the ear to hear other sounds.

16. (original) In the ear mounting assembly for an electronic component as in claim 15, including means on the clamping section to adjust the force for holding the backing means and electronic component in assembled position.

17. (currently amended) In the ear mounting assembly for electronic components as in claims 15, wherein the ear pad has an oval-shaped face at the end remote from the end connected to the arcuate section to enable the ear pad to be fitted into the cavity of the ear when the ear mounting assembly is connected to the ear for passing the audio sounds, signals and communications to the auditory canal of the ear.

18. (currently amended) An electronic headset, comprising:

a housing having at least one opening disposed therein and an endface defining a surface at which said at least one opening terminates, said housing being positionable at least partially within an ear of a user such that said endface rests within the user's ear and such that said at least one opening is directed towards the auditory canal within the user's ear;

electronic circuitry arranged within said housing, said circuitry being adapted to convert electronic signals ~~acoustic energy~~ into acoustic energy signals; and

a clamp-connecting member coupled to said housing and operable to move toward said endface surface ~~between to~~ a first position proximate the ear lobe of the user such that the electronic headset is secured against the ear of the user and away from said endface surface to a second position such that the electronic head set may be removed from the ear of the user, and

~~wherein said housing includes an extended portion, said at least one opening arranged through said extended portion, said extended portion being positionable substantially adjacent the auditory canal of a user's ear without entirely occluding the auditory canal.~~

19. (previously presented) The electronic headset of claim 18 wherein said clamp-connecting member is pivotably mounted to said housing.

20. (previously presented) The electronic headset of claim 19 wherein said clamp connecting member is pivotably mounted to said housing using an assembly that allows a force exerted on the user's ear lobe to be adjusted.

21. (currently amended) The electronic headset of claim 18 wherein said housing includes an extended portion and a mounting member projecting from said extended portion, said mounting member including an arcuate neck portion which provides a resting surface for the housing against the user's ear.

22. (currently amended) The electronic headset of claim 18 wherein housing includes a mounting member connected to said extended portion such that said mounting member fits in the concha of the user's ear.

23. (previously presented) The electronic headset of claim 18 wherein housing includes a mounting member detachably connected to said extended portion such that said mounting member fits in the concha of the user's ear.

24. (cancelled).

25. (currently amended) The electronic headset of claim ~~24~~18 wherein said electronic circuitry is adapted to receive sound from a microphone disposed within said housing.

26. (cancelled).

27. (new) An earpiece, comprising:

a housing having a body extending between a first end and a second end,

the first end comprising a mounting member having an endface surface, the mounting member being adapted to rest in a user's ear and to project in a first direction towards the auditory canal of the user's ear when resting in the user's ear,

the endface surface defining a plane that extends in a second direction and a third direction, the second and third directions being substantially perpendicular to each other and the first direction,

the body including at least one passageway that terminates proximate the first end; and

a member connected to the housing proximate the second end for clamping the earpiece to the user's ear lobe, the member being movable away from the plane defined by the endface surface and operable to secure the earpiece against the user's ear lobe.

28. (new) The earpiece of claim 27, wherein the housing extends generally downwardly when the earpiece is resting in the user's ear and the user is oriented in an upright position.

29. (new) The earpiece of claim 27, further comprising an ear section that is adapted to be mounted to the first end and project towards the auditory canal.

30. (new) The earpiece of claim 27, further comprising a pad that is adapted to fit over the first end.